

Electrical data Multi-turn actuators for open-close duty with 3-phase AC motors
Short-time duty S2 - 15 min, 400 V/50 Hz

SA 07.2 – SA 16.2

Multi-turn actuator			Motor									
Type	Speed rpm	Torque max. Nm	Type	Power P _N (kW)	Speed rpm	Nominal current ¹⁾ I _N (A)	Current ²⁾ approx. I _{max} (A)	Starting current I _A (A)	cos φ	Setting Overcurrent prot. device (A)	AUMA Power class	
											Contact ³⁾	Thyristor ³⁾
SA 07.2	4	30	VD00063-4-0.02	0.02	1,400	0.4	0.3	1.0	0.40	0.3	A1	B1
	5.6		VD00063-4-0.02	0.02	1,400	0.4	0.4	1.0	0.40	0.4	A1	B1
	8		VD00063-4-0.04	0.04	1,400	0.4	0.4	1.0	0.50	0.4	A1	B1
	11		VD00063-4-0.04	0.04	1,400	0.4	0.5	1.0	0.50	0.5	A1	B1
	16		VD00063-2-0.06	0.06	2,800	0.6	0.6	1.9	0.57	0.6	A1	B1
	22		VD00063-2-0.06	0.06	2,800	0.6	0.7	1.9	0.57	0.7	A1	B1
	32		AD00063-4-0.10	0.10	1,400	1.0	1.0	2.4	0.42	1.0	A1	B1
	45		AD00063-4-0.10	0.10	1,400	1.0	1.0	2.4	0.42	1.0	A1	B1
	63		AD00063-2-0.20	0.20	2,800	0.8	1.2	4.4	0.60	1.2	A1	B1
	90		AD00063-2-0.20	0.20	2,800	0.8	1.3	4.4	0.60	1.3	A1	B1
125	AD00063-2-0.30	0.30	2,800	0.9	1.5	4.4	0.70	1.5	A1	B1		
180	AD00063-2-0.30	0.30	2,800	0.9	1.6	4.4	0.70	1.6	A1	B1		
SA 07.6	4	60	VD00063-4-0.03	0.03	1,400	0.4	0.4	1.0	0.43	0.4	A1	B1
	5.6		VD00063-4-0.03	0.03	1,400	0.4	0.5	1.0	0.43	0.5	A1	B1
	8		VD00063-4-0.06	0.06	1,400	0.6	0.7	1.6	0.38	0.7	A1	B1
	11		VD00063-4-0.06	0.06	1,400	0.6	0.7	1.6	0.38	0.7	A1	B1
	16		VD00063-2-0.12	0.12	2,800	0.7	0.9	3.0	0.52	0.9	A1	B1
	22		VD00063-2-0.12	0.12	2,800	0.7	1.0	3.0	0.52	1.0	A1	B1
	32		AD00063-4-0.20	0.20	1,400	1.6	1.9	4.6	0.42	1.9	A1	B1
	45		AD00063-4-0.20	0.20	1,400	1.6	2.0	4.6	0.42	2.0	A1	B1
	63		AD00063-2-0.40	0.40	2,800	1.6	2.3	9.0	0.53	2.3	A1	B1
	90		AD00063-2-0.40	0.40	2,800	1.6	2.5	9.0	0.53	2.5	A1	B1
125	AD00063-2-0.50	0.50	2,800	1.7	3.0	9.0	0.62	3.0	A1	B1		
180	AD00063-2-0.50	0.50	2,800	1.7	3.2	9.0	0.62	3.2	A1	B1		
SA 10.2	4	120	VD00071-4-0.06	0.06	1,400	0.5	0.6	2.0	0.40	0.6	A1	B1
	5.6		VD00071-4-0.06	0.06	1,400	0.5	0.6	2.0	0.40	0.6	A1	B1
	8		VD00071-4-0.12	0.12	1,400	1.0	1.1	3.0	0.40	1.1	A1	B1
	11		VD00071-4-0.12	0.12	1,400	1.0	1.2	3.0	0.40	1.2	A1	B1
	16		VD00071-2-0.25	0.25	2,800	1.3	1.5	4.5	0.52	1.5	A1	B1
	22		VD00071-2-0.25	0.25	2,800	1.3	1.8	4.5	0.52	1.8	A1	B1
	32		AD00071-4-0.40	0.40	1,400	2.5	2.6	8.5	0.42	2.6	A1	B1
	45		AD00071-4-0.40	0.40	1,400	2.5	3.0	8.5	0.42	3.0	A1	B1
	63		AD00071-2-0.70	0.70	2,800	3.0	3.6	16	0.54	3.6	A1	B1
	90		AD00071-2-0.70	0.70	2,800	3.0	4.0	16	0.54	4.0	A1	B1
125	AD00071-2-1.00	1.00	2,800	3.5	5.2	16	0.64	5.2	A1	B1		
180	AD00071-2-1.00	1.00	2,800	3.5	5.5	16	0.64	5.5	A1	B1		
SA 14.2	4	250	VD00090-4-0.12	0.12	1,400	0.5	0.8	2.8	0.60	0.8	A1	B1
	5.6		VD00090-4-0.12	0.12	1,400	0.5	1.0	2.8	0.60	1.0	A1	B1
	8		VD00090-4-0.25	0.25	1,400	1.0	1.6	5.2	0.60	1.6	A1	B1
	11		VD00090-4-0.25	0.25	1,400	1.0	1.7	5.2	0.60	1.7	A1	B1
	16		VD00090-2-0.45	0.45	2,800	1.5	3.0	9.0	0.64	3.0	A1	B1
	22		VD00090-2-0.45	0.45	2,800	1.5	3.5	9.0	0.64	3.5	A1	B1
	32		AD00090-4-0.75	0.75	1,400	2.5	4.0	16	0.62	4.0	A1	B1
	45		AD00090-4-0.75	0.75	1,400	2.5	5.0	16	0.62	5.0	A1	B1
	63		AD00090-2-1.40	1.40	2,800	4.7	7.0	38	0.60	7.0	A2	B2
	90		AD00090-2-1.40	1.40	2,800	4.7	9.0	38	0.60	9.0	A2	B2
125	AD00090-2-1.80	1.80	2,800	5.3	11	38	0.65	11	A2	B2		
180	AD00090-2-1.80	1.80	2,800	5.3	11	38	0.65	11	A2	B2		
SA 14.6	4	500	VD00090-4-0.20	0.20	1,400	0.9	0.9	5.2	0.54	0.9	A1	B1
	5.6		VD00090-4-0.20	0.20	1,400	0.9	1.0	5.2	0.54	1.0	A1	B1
	8		VD00090-4-0.40	0.40	1,400	1.7	3.0	9.3	0.56	3.0	A1	B1
	11		VD00090-4-0.40	0.40	1,400	1.7	3.5	9.3	0.56	3.5	A1	B1
	16		VD00090-2-0.80	0.80	2,800	3.6	5.0	18	0.51	5.0	A1	B1
	22		VD00090-2-0.80	0.80	2,800	3.6	5.5	18	0.51	5.5	A1	B1
	32		AD00090-4-1.60	1.60	1,400	5.3	7.5	38	0.57	7.5	A2	B2
	45		AD00090-4-1.60	1.60	1,400	5.3	9.0	38	0.57	9.0	A2	B2
	63		AD00090-2-3.00	3.00	2,800	9.0	13	58	0.60	13	A2	B3
	90		AD00090-2-3.00	3.00	2,800	9.0	16	58	0.60	16	A2	B3
125	AD00090-2-3.30	3.30	2,800	9.5	21	58	0.65	19	A2	B3		
180	AD00090-2-3.30	3.30	2,800	9.5	22	58	0.65	19	A2	B3		
SA 16.2	4	1,000	VD00112-4-0.40	0.40	1,400	1.4	2.7	10	0.65	2.7	A1	B1
	5.6		VD00112-4-0.40	0.40	1,400	1.4	2.9	10	0.65	2.9	A1	B1
	8		VD00112-4-0.80	0.80	1,400	2.8	5.0	22	0.57	5.0	A1	B2
	11		VD00112-4-0.80	0.80	1,400	2.8	5.5	22	0.57	5.5	A1	B2
	16		VD00112-2-1.50	1.50	2,800	4.8	8.7	40	0.60	8.7	A2	B2
	22		VD00112-2-1.50	1.50	2,800	4.8	10	40	0.60	10	A2	B2
	32		AD00112-4-3.00	3.00	1,400	8.5	13	60	0.71	13	A2	B3
	45		AD00112-4-3.00	3.00	1,400	8.5	16	60	0.71	16	A2	B3
	63		AD00112-2-5.00	5.00	2,800	11	25	120	0.80	25	A2	–
	90		AD00112-2-5.00	5.00	2,800	11	30	120	0.80	26	A2	–
125	AD00112-2-6.00	6.00	2,800	12	35	120	0.83	26	A2	–		
180	AD00112-2-6.00	6.00	2,800	12	45	120	0.83	26	A2	–		

1) Current at operating torque (corrsponds to approx. 35 % of maximum torque)
 2) Current at max. torque. We recommend to select switchgears according to these values.
 3) Assignment of switchgears when using AUMA controls of types AUMA AUMA MATIC and AUMATIC. For selection of switchgears for actuators in NORM version, please refer to notes on page 2.

We reserve the right to alter data according to improvements made. Previous documents become invalid with the issue of this document.

Motor data is approximate. Due to usual manufacturing tolerances, there may be deviations from the values given.

The permissible fluctuation of the nominal voltage is $\pm 10\%$. If the voltage drops below, there is a reduction of the nominal output torque.

To protect against overheating, thermostiches or PTC thermistors are embedded in the motor windings. For actuators without integral controls (AUMA NORM), these have to be connected to the external control circuit (see terminal plan). If thermostiches or PTC thermistors are not connected, this voids our warranty for the motor.

Rating of the thermostiches:

AC		DC	
250 V, 50 – 60 Hz		60 V	1.0 A
cos φ = 1	2.5 A	42 V	1.2 A
cos φ = 0.6	1.6 A	24 V	1.5 A

For further details refer to “Technical data Multi-turn actuators SA 07.2 – SA 16.2 for open-close duty with 3-phase AC motors“.

Assigning switchgears for NORM version (without AUMA controls)

We recommend to specify switchgears according to their rated power/motor power in compliance with the assigned AUMA power class.

AUMA power class	Rated power contactor acc. to IEC AC-3 400 V AC	Motor power contactor acc. to UL/CSA for	
		480 V AC	600 V AC
A1	4.0 kW	5.0 hp	5.0 hp
A2	7.5 kW	10 hp	10 hp
A3	15 kW	20 hp	25 hp
A4	30 kW	60 hp	60 hp
A5	55 kW	75 hp	100 hp

We reserve the right to alter data according to improvements made. Previous documents become invalid with the issue of this document.